

.TF

Lighting towers

Mobile Lighting Towers with Diesel or Hybrid Generator
Suitable for Generators and Without Generators



ELCOS
POWER GENERATORS



Emergency Response
Pronto Intervento



Construction sites
Siti di costruzioni



Special Events
Eventi pubblici

**Designed to be easy to move and robust,
they offer fuel efficiency and reliability**

Equipped with LED, Metal Halide or Halogen Floodlights
9 mt high with manual or automatic raising system

***Torri faro mobili realizzate per essere
mobili e robuste, offrono la miglior qualità***

*Equipaggiate con riflettori LED, Ioduri Metallici o Alogeni
Fino a 9 mt di altezza con alzata automatica o manuale*

www.elcos.net

.TF

Mobile Lighting Towers with Diesel Generator, with Hybrid Generator Suitable for Generators and Without Generators

Torri faro mobili con Generatore Diesel, con Generatore ibrido
Predisposte per Generatore e senza Generatore



HEIGHT mts

RAISING

SPEED km/h

N° WATT

TYPE

TROLLEY

ILLUMINATED AREA sqm

ENGINE

CODE

CYLINDERS

CONSUMPTION

Mobile Lighting Towers With Generator - Torri faro mobili con Generatore

TF M 4X150L.TL	9	Manual	80	4	150	LED	Off road	3000	Kubota	Z482	2	0,55
TF M 4X1000M.TL	9	Manual	110	4	1000	Metal Halide	Off road	4200	Kubota	D-1105	3	1,85
TF H 6X150L.TL	9	Hydraulic	120	6	150	LED	Low speed	3800	Kubota	Z482	2	0,55
TF H 6X150L.TV	9	Hydraulic	120	6	150	LED	Fast speed	3800	Kubota	Z482	2	0,55

Mobile Lighting Towers With Hybrid Generator - Torri faro mobili con generatore ibrido

TH H 6 x 150L.TL	9	Hydraulic	110	6	150	LED	Fast speed	3800	Kubota	Z482	2	0,55
------------------	---	-----------	-----	---	-----	-----	------------	------	--------	------	---	------

Mobile Lighting Towers Suitable for Generators - Torri faro mobili adattabili con generatori

TC M 4X1500A.TL	9	Manual	105	4	1500	Halogen	Low speed	2400	suitable for GS from 10 to 4			
TC H 4X1500A.TL	9	Hydraulic	105	4	1500	Halogen	Low speed	2400	suitable for GS from 10 to 4			
TC H 4X1000M.TL	9	Hydraulic	105	4	1000	Metal Halide	Low speed	4200	suitable for GS from 10 to 4			

Lighting Towers Without Generator - Torri faro senza generatore


TP M 4x150L.CA	7	Manual	115	4	150	LED	Hand trolley	2400	-	-	-	-
TP M 4x300L.BF	9	Manual	110	4	300	LED	Base frame	4500	-	-	-	-



Mobile Lighting Towers with Diesel Generator
Torri faro mobili con Generatore Diesel

Mobile Lighting Towers with Hybrid Generator
Torri faro mobili con Generatore Ibrido

Mobile Lighting Towers suitable for Generators
Torri faro mobili predisposte per Generatori



Linz	3,5	256x135x255	256x255x900	750	80	145	60
Linz	8	256x135x255	256x255x900	795	80	43	64
Linz	3,5	240x140x245	240x178x850	936	110	200	65
Linz	3,5	240x140x245	240x178x850	936	110	200	65

Linz	3,5	295x145x257	295x293x900	1300	222	700	65
------	-----	-------------	-------------	------	-----	-----	----

0 kVA SS/RB - predisposte per GE da 10 a 40 kVA SS/RB	-	-	-	-
0 kVA SS/RB - predisposte per GE da 10 a 40 kVA SS/RB	-	-	-	-
0 kVA SS/RB - predisposte per GE da 10 a 40 kVA SS/RB	-	-	-	-

-	-	120x85x210	185x145x700	300	-	-	-
-	-	110x110x265	236x236x900	445	-	-	-



**Lighting Towers
with Generator**
Torri faro predisposte per Generatore

**Lighting Towers Stationary
without Generator**
Torri faro stazionarie senza Generatore



ELCOS
POWER GENERATORS

ELCOS SRL
Strada Statale 234 Km 58.250 -
26023 Grumello Cremonese CR - Italy
tel +39 0372 72330 - fax +39 0372 7233220
PI 01084730199
info@elcos.net - elcos@pec.elcos.net



assistenza@elcos.net
+39.0372.7233300
elcos.net/service



www.elcos.net